



LC/SC Angle Boot

Connector Kit



Features

- High return loss
- Low insertion loss
- Compact, simple style interface
- Compliant with TIA/IEA, IEC, RoHS

Applications

- CATV, LANs, Telecom, Video
- Active device termination
- Telecommunication networks
- Gigabit applications (ATM, Ethernet)

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Return Loss	≥55dB	≥20dB	≥65dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.2 dB typical change, 500 matings		
Available Wavelengths	SM=1310 & 1550nm, MM=850nm		

MU

Connector Kit



Features

- High return loss
- Low insertion loss
- Compact, NTT & JIS compliant
- Compliant with TIA/IEA, IEC, RoHS


Applications

- CATV, LANs, Telecom, Video
- Active device termination
- Telecommunication networks
- Gigabit applications (ATM, Ethernet)

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Return Loss	≥55dB	≥20dB	≥65dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.2 dB typical change, 500 matings		
Available Wavelengths	SM=1310 & 1550nm , MM=850nm		

Ordering choice

- ▶ Simplex / Duplex
- ▶ Connector Size
2.0mm, 3.0mm
- ▶ Boot color
Blue, White, Black, Red
Yellow, Green, Beige, Aqua
- ▶ Ferrule I.D size
125um, 125.5um
126um, 127um



Ordering choice

- ▶ Simplex / Duplex
Pigtail
- ▶ Connector Size
0.9mm, 2.0mm
- ▶ Boot color
Blue
- ▶ Ferrule I.D size
125um, 125.5um
126um, 127um
- ▶ MU-J Style