

E-2000

Connector Kit



Features

- High return loss
- Low insertion loss
- High bit-rate protocols
- Compliant with TIA/IEA, IEC, RoHS

Applications

- CATV, LANs, Telecom, Video
- Active device termination
- Telecommunication networks
- Gigabit applications (ATM, Ethernet)

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Return Loss	≥55dB	≥20dB	≥65dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.2 dB typical change, 500 matings		
Available Wavelengths	SM=1310 & 1550nm , MM=850nm		

MTRJ

Connector Kit



Features

- High return loss
- Low insertion loss
- Telcordia style boots
- Compliant with TIA/IEA, IEC, RoHS

Applications

- CATV, Metro, LANs
- Active device termination
- Telecommunication networks
- Industrial, medical, & military

Specifications	Single mode	Multi mode
Insertion Loss	≤0.2dB	≤0.2dB
Return Loss	≥55dB	≥20dB
Operating Temperature	-40 °C to +75 °C	
Durability	≤0.1 dB typical change, 500 matings	
Available Wavelengths	SM=1310 & 1550nm, MM=850nm	

Ordering choice

- ▶ Simplex / Duplex Pigtail
- ▶ Connector Size
0.9mm, 2.0mm, 3.0mm
- ▶ Boot color
Blue, Green, Black
- ▶ Ferrule I.D size
125um, 125.5um
126um, 127um

Ordering choice

- ▶ Boot color
Black & other colors
- ▶ Zipcord 2.0mm only
- ▶ Male & Female Type