

## SC-PC MM

## Patch Cord



### Features

- High return loss
- Low insertion loss
- Telcordia style boots
- Compliance with TIA/IEA, IEC, RoHS

### Applications

- CATV, Metro, LANs
- Active device termination
- Telecommunication networks
- Industrial, medical, & military

Specifications	PC (Standard)	PC (Special)
Insertion Loss	≤0.3dB	≤0.2dB
Return Loss	≥20dB	≥20dB
Operating Temperature	-40 °C to +75 °C	
Durability	≤0.1 dB typical change, 500 matings	
Available Wavelengths	MM=850nm	

## FC-UPC

## Patch Cord



### Features

- High return loss
- Low insertion loss
- Telcordia style boots
- Compliance with TIA/IEA, IEC, RoHS

### Applications

- CATV, Metro, LANs
- Active device termination
- Telecommunication networks
- Industrial, medical, & military

Specifications	UPC (Standard)	UPC (Special)
Insertion Loss	≤0.25dB	≤0.25dB
Return Loss	≥50dB	≥55dB
Operating Temperature	-40 °C to +75 °C	
Durability	≤0.1 dB typical change, 500 matings	
Available Wavelengths	SM=1310 & 1550nm	

### Ordering choice

- ▶ Fan-out patch cord
- ▶ Simplex / Duplex Pigtail
- ▶ 12 color Cable
- ▶ Loose & Tight Buffer
- ▶ Boot Color
- ▶ Cable Size 0.9mm, 1.8mm, 2.0mm 3.0mm
- ▶ Packing Style
- ▶ Label Style
- ▶ Bend-insensitive G652D, G657A
- ▶ OFNR & LSZH & OFNP
- ▶ OM1, OM2, OM3, OM4

### Ordering choice

- ▶ Fan-out patch cord
- ▶ Simplex / Duplex Pigtail
- ▶ 12 color Cable
- ▶ Loose & Tight Buffer
- ▶ Boot Color
- ▶ Cable Size 0.9mm, 1.8mm, 2.0mm 3.0mm
- ▶ Packing Style
- ▶ Label Style
- ▶ Bend-insensitive G652D, G657A
- ▶ Key Ring
- ▶ Tunable & Fixed
- ▶ OFNR & LSZH & OFNP