

SC Simplex

Adaptor



Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

SC Duplex

Adaptor



Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

SC Metal

Adaptor



Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

Ordering choice

- ▶ Sleeve
 - Zirconia & PB
- ▶ Adaptor Color
 - Blue, Green, Beige, Aqua and other colors
- ▶ Adaptor Flange
 - Flange & No Flange type

Ordering choice

- ▶ Sleeve
 - Zirconia & PB
- ▶ Adaptor Color
 - Blue, Green, Beige, Aqua and other colors
- ▶ Adaptor Flange
 - Flange & No Flange type

Ordering choice

- ▶ Sleeve
 - Zirconia & PB
- ▶ Adaptor Flange
 - Flange & No Flange type