



## ST

## Adaptor



### Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

### Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

### Ordering choice

- ▶ Sleeve
  - Zirconia & PB
- ▶ Adaptor Material
  - Metal & Plastic

## ST Duplex

## Adaptor



### Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

### Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

### Ordering choice

- ▶ Sleeve
  - Zirconia & PB
- ▶ Adaptor Material
  - Metal & Plastic

## DIN

## Adaptor



### Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

### Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

### Ordering choice

- ▶ Sleeve
  - Zirconia & PB