

LC Simplex

Adaptor



Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

| Specifications | Single mode | Multi mode | APC |
|-----------------------|-------------------------------------|------------|--------|
| Insertion Loss | ≤0.2dB | ≤0.2dB | ≤0.2dB |
| Operating Temperature | -40 °C to +75 °C | | |
| Durability | ≤0.1 dB typical change, 500 matings | | |

LC DX Foot Print

Adaptor



Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

| Specifications | Single mode | Multi mode | APC |
|-----------------------|-------------------------------------|------------|--------|
| Insertion Loss | ≤0.2dB | ≤0.2dB | ≤0.2dB |
| Operating Temperature | -40 °C to +75 °C | | |
| Durability | ≤0.1 dB typical change, 500 matings | | |

LC DX Foot Print w/o Flange

Adaptor



Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

| Specifications | Single mode | Multi mode | APC |
|-----------------------|-------------------------------------|------------|--------|
| Insertion Loss | ≤0.2dB | ≤0.2dB | ≤0.2dB |
| Operating Temperature | -40 °C to +75 °C | | |
| Durability | ≤0.1 dB typical change, 500 matings | | |

Ordering choice

- Sleeve
 - Zirconia & PB
- Adaptor Color
 - Blue, Green, Beige, Aqua and other colors

Ordering choice

- Sleeve
 - Zirconia & PB
- Adaptor Color
 - Blue, Green, Beige, Aqua and other colors

Ordering choice

- Sleeve
 - Zirconia & PB
- Adaptor Color
 - Blue, Green, Beige, Aqua and other colors