

## LC Low Profile

## Adaptor



### Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

### Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

### Ordering choice

- ▶ Sleeve  
Zirconia & PB
- ▶ Adaptor Color  
Blue, Green, Beige,  
Aqua, and other colors

## LC Quad

## Adaptor



### Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

### Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

### Ordering choice

- ▶ Sleeve  
Zirconia & PB
- ▶ Adaptor Color  
Blue, Green, Beige,  
Aqua, and other colors

## MTRJ SC Foot Print

## Adaptor



### Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

### Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	PC MM
Insertion Loss	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C	
Durability	≤0.1 dB typical change, 500 matings	

### Ordering choice

- ▶ Adaptor Color - Black