



E 2000

Adaptor



Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

Ordering choice

- ▶ Sleeve
Zirconia & PB
- ▶ Adaptor Color
Blue, Green, Beige

FC/ST

Adaptor



Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

Ordering choice

- ▶ Sleeve
Zirconia & PB

LC/FC Metal

Adaptor



Features

- High return loss
- Low insertion loss
- 100% Optic test (Insertion Loss)

Applications

- CATV, Metro, LANs, & military
- Active device termination
- Telecommunication networks

Specifications	Single mode	Multi mode	APC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.1 dB typical change, 500 matings		

Ordering choice

- ▶ Sleeve
Zirconia & PB