

MU

Patch Cord



Features

- High return loss
- Low insertion loss
- Compact, NTT, & JIS compliant
- Compliant with TIA/IEA, IEC, RoHS

Applications

- CATV, LANs, Telecom, Video
- Active device termination
- Telecommunication networks
- Gigabit applications (ATM, Ethernet)

Specifications	UPC SM	PC MM	APC SM
Insertion Loss	≤0.25dB	≤0.3dB	≤0.25dB
Return Loss	≥55dB	≥20dB	≥65dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.2 dB typical change, 500 matings		
Available Wavelengths	SM=1310 & 1550nm, MM=850nm		

Ordering choice

- ▶ Fan-out patch cord
- ▶ Simplex / Duplex Pigtail
- ▶ 12 color Cable
- ▶ Loose & Tight Buffer
- ▶ Boot Color
- ▶ Cable Size 0.9mm, 1.8mm, 2.0mm
- ▶ Packing Style
- ▶ Label Style
- ▶ OM1, OM2, OM3, OM4
- ▶ OFNR & LSZH & OFNP
- ▶ Bend-insensitive G652D, G657A
- ▶ MU-J Style
- ▶ Angle = 8°

E 2000

Patch Cord



Features

- High return loss
- Low insertion loss
- High bit-rate protocols
- Compliant with TIA/IEA, IEC, RoHS

Applications

- CATV, LANs, Telecom, Video
- Active device termination
- Telecommunication networks
- Gigabit applications (ATM, Ethernet)

Specifications	UPC SM	PC MM	APC SM
Insertion Loss	≤0.25dB	≤0.3dB	≤0.25dB
Return Loss	≥55dB	≥20dB	≥65dB
Operating Temperature	-40 °C to +75 °C		
Durability	≤0.2 dB typical change, 500 matings		
Available Wavelengths	SM=1310 & 1550nm, MM=850nm		

Ordering choice

- ▶ Fan-out patch cord
- ▶ Simplex / Duplex Pigtail
- ▶ 12 color Cable
- ▶ Loose & Tight Buffer
- ▶ Boot Color
- ▶ Cable Size 0.9mm, 1.8mm, 2.0mm 3.0mm
- ▶ Packing Style
- ▶ Label Style
- ▶ Angle = 8°
- ▶ OM1, OM2, OM3, OM4
- ▶ OFNR & LSZH & OFNP
- ▶ Bend-insensitive G652D, G657A